



(800) 720-5256

Quartz Infrared Lamp

Standard T-3 Sizes

Model Number	LAMP TYPE						End Contact	Colour Temperature (±100K)
	Watts	Volts	Overall Length		Heated Length			
			mm	in.	mm	in.		
5625115340	250	115	340	13.3	256	10.2	R7	2400
5630230117	300	230	117	4.6	60	2.3	R7	2500
5630240220	300	240	220	8.6	155	6.10	R7	2200
5630240212	300	240	212J	8.3	155	6.10	Z	2200
5640240186	400	240	186	7.3	130	5.1	R7	2300
5650115225	500	115	225	8.8	120	4.7	R7	2350
5650120200	500	120	200	7.8	122	4.8	R7	2400
5650120208	500	120	208	8.1	127	5	R7	2250
5650240206	500	240	206	8.1	155	6.10	n/a	2500
5650240212	500	240	212	8.3	124	4.8	R7	2500
5650240215	500	240	215	8.4	124	4.8	R7	2500
5650240220	500	240	220	8.6	155	6.10	R7	2500
5650240227	500	240	227	8.9	165	6.4	SK-15	2500
5650240212	500	240	212J	8.3	165	6.4	Z	2500
5660220610	600	220	610	24	545	21.4	R7	2400
5670240210	700	240	210	8.2	148	5.8	Z	2400
5675240220	750	240	220	8.6	155	6.10	R7	2400
5690120580	900	120	580	22.8	395	15.5	R7	2400
5690220615	900	220	615	24.2	510	20.0	R7	2200
5610115340	1000	115	340	13.3	272	10.7	R7	2400
5610120119	1000	120	119	4.68	63	2.48	n/a	3000
5610220518	1000	220	518	20.3	465	18.3	R7	2100
5610230350	1000	230	350	13.7	280	11.0	n/a	2400
5610230357	1000	230	357	14.0	272	10.7	SK-15	2400
5610230370	1000	230	370	14.5	272	10.7	X	2400
5610230373	1000	230	373	14.6	272	10.7	Z	2400
5610230373	1000	230	373	14.6	272	10.7	R7	2400
5610230400	1000	230	400	15.7	298	11.7	R7	2000
5610235215	1000	235	215	8.46	150	5.90	Z	2600
5610235370	1000	235	370	14.5	272	10.7	n/a	2400
5610240220	1000	240	220	8.66	155	6.10	R7	2500
5610240245	1000	240	245	9.64	174	6.85	R7	2400
5610240340	1000	240	340	13.3	272	10.7	R7	2400

Model Number	Watts	Volts	Overall Length		Heated Length		End Contact	Colour Temperature (±100K)
			mm	in.	mm	in.		
5610240348	1000	240	348	13.7	250	9.84	R7	2400
5610240354	1000	240	354	13.9	264	10.3	R7	2400
5610240626	1000	240	626	24.6	505	19.8	R7	2400
5610400357	1000	400	357	14.0	272	10.7	SK-15	2400
5610416348	1000	416	348	13.7	250	9.84	R7	2400
5612144225	1200	144	225	8.85	160	6.29	SS	2500
5612235224	1200	235	224	8.81	155	6.10	Z	2700
5612400224	1200	400	224	8.81	135	5.31	SK-15	2550
5615110166	1500	110	166	6.53	91	3.58	R7	2900
5615220450	1500	220	450	17.7	355	13.9	R7	2500
5615240495	1500	240	495	19.4	415	16.3	SK-15	2400
5615240626	1500	240	626	24.6	510	20.0	R7	2250
5615240626	1500	240	626	24.6	550	21.6	SK-15	2250
5615245189	1500	245	189	7.44	125	4.92	R7	2900
5615400500	1500	400	500	19.6	400	15.9	SK-15	2450
5615400570	1500	400	570	22.4	500	19.6	R7	2300
5615210440	1500	210	440	17.3	375	14.7	SK-15	2500
5615230445	1530	230	445	17.5	378	14.8	SK-15	2500
5616144220	1600	144	220	8.66	158	6.22	SK-15	2600
5616230500	1600	230	500	19.6	401	15.7	Z	2550
5616230500	1600	230	500	19.6	405	15.9	SK-15	2550
5616235224	1600	235	224	8.81	155	6.10	Z	2750
5616240500	1600	240	500	19.6	404	15.9	R7	2500
5616416500	1600	416	500	19.6	404	15.9	R7	2500
5616450582	1600	450	582	22.9	492	19.3	R7	2400
5618416688	1800	416	688	27.0	576	22.6	R7	2400
5618416690	1800	416	690	27.1	610	24.0	X	2200
5620207348	2000	207	348	13.7	273	10.7	n/a	2500
5620230224	2000	230	224	8.81	155	6.10	SK-15	2950
5620230357	2000	230	357	14.0	280	11.0	SK-15	2300
5620230373	2000	230	373	14.6	273	10.7	SK-15	2300
5620230373	2000	230	373	14.6	273	10.7	R7	2300
5620230373	2000	230	373	14.6	273	10.7	SK-15	2250
5620230400	2000	230	400	15.7	300	11.8	R7	2500
5620230550	2000	230	550	21.6	500	19.6	SK-15	2300
5620240307	2000	240	307	12.0	237	9.33	n/a	2550
5620240340	2000	240	340	13.3	280	11.0	n/a	2500
5620240340	2000	240	350	13.7	250	9.84	SS	2500
5620240370	2000	240	370	14.5	280	11.0	X	2300
5620240626	2000	240	626	24.6	509	20.0	SK-15	2500
5620240626	2000	240	626	24.6	505	19.8	SK-15	2450
5620240800	2000	240	800	31.4	700	27.5	R7	2400
5620400307	2000	400	307	12.0	243	9.56	R7	2500

Model Number	Watts	Volts	Overall Length		Heated Length		End Contact	Colour Temperature (±100K)
			mm	in.	mm	in.		
5620400354	2000	400	354	13.9	280	11.0	SK-15	2500
5620400357	2000	400	357	14.0	280	11.0	SK-15	2600
5620400508	2000	400	508	20.0	410	16.1	X	2450
5620400580	2000	400	580	22.8	520	20.4	SK-15	2450
5620400580	2000	400	580	22.8	510	20.0	SK-15	2400
5620416626	2000	416	626	24.6	505	19.8	R7	2300
5625230307	2500	230	307	12.0	245	9.64	SK-15	2800
5625416728	2500	416	728	28.6	600	23.6	R7	2400
5625416106	2500	416	1060	41.7	970	38.1	R7	2300
5625480732	2500	480	732	28.8	635	25.0	R7	2300
5630240500	3000	240	500	19.6	410	16.1	R7	2400
5630240626	3000	240	626	24.6	509	20.0	R7	2500
5630240626	3000	240	626	24.6	509	20.0	SK-15	2500
5630401110	3000	401	1100	43.3	1000	39.3	SK-15	2250
5630416875	3000	416	875	34.4	760	29.9	R7	2400
5630416900	3000	416	900	35.4	800	31.4	R7	2400
5630416115	3000	416	1150	45.2	1050	41.3	R7	2500
5630416124	3000	416	1242	48.8	1145	45.0	R7	2100
5632416926	3200	416	926	36.4	804	31.6	R7	2400
5635416142	3500	416	1425	56.1	1320	51.9	R7	2000
5636416101	3600	416	1018	40.0	904	35.5	R7	2400
5636480105	3650	480	1056	41.5	955	37.5	R7	2400
5638570105	3800	570	1050	41.3	950	37.4	R7	2400
5640400800	4000	400	800	23.6	500	19.6	R7	2400
5640416112	4000	416	1120	44.0	1002	39.4	R7	2400
5640416163	4000	416	1630	64.1	1524	60.0	R7	2000
5653400600	5300	400	600	23.6	500	19.6	R7	2400
5654480230	5400	480	230	9.05	208	8.18	R7	3000
5655400112	5500	400	1125	44.2	1000	39.3	SL-15	2600
56554000113	5500	400	1130	44.4	1060	31.7	SK-15	2550
5662416270	6200C	416	270	10.6	250	9.84	R7	3000
5662416455	6250C	416	455	17.9	434	17.0	R7	3000